MDE/MDG28PD SUPER-CAPACITY DRYER





MICROPROCESSOR CONTROLS

- Provides simple programming options for owner: including adjustable cycle price, cycle time, diagnostics and vend count.
- Easy one-touch cycle selection for customers.

TURBOVENT™ DRYER TECHNOLOGY

- Additional blower wheel provides exceptional performance in long vents.
- High airflow reduces dry time.





PORCELAIN-ENAMEL TOP

Durable finish for high-use environments.



CLOTHESPIN™ APP BY MAYTAG COMPATIBLE

- Customers will love how convenient it is to do their laundry with the new Clothespin[™] app by Maytag.
- They can use their smartphones to pay for their laundry, remotely check for available washers and dryers, and receive a notification when their laundry cycles are complete.*



5-YEAR LIMITED WARRANTY

• All parts are covered for 5 years.**



- *Subject to terms of use and privacy policy.

 Message and data rates may apply. In Canada,
 Maytag Connect 360°™ compatible only.
- **See maytagcommerciallaundry.com for complete warranty for details.











OUR COMMITMENT TO DEPENDABLE QUALITYFor well over 50 years, Maytag® Commercial Laundry has promised and delivered dependability. We create that quality by making durable washers and dryers, built to endure heavy use and last for years. We design our machines to perform reliably and to produce consistent results. Finally, we give our washers and dryers the power to do their jobs thoroughly, cleaning and drying laundry quickly and efficiently-and justifying the trust that has been placed in us for generations.

MAYTAG® SUPER-CAPACITY DRYER

MICROPROCESSOR CONTROLS, COIN-DROP


DRYER SPECIFICATIONS		
MODEL	MDE/MDG28PD	
MOTOR		
Single-phase, thermoprotected against overload, auto-reset	Yes	
HP (kw)	¹⅓ (.25)	
Tumble speed—RPM	50 ± 1	
CAPACITY		
Cu. ft. (liters)	6.7 (190)	
AIRFLOW		
Gas models—cfm (cmm)	230 (6.5)	
Electric models—cfm (cmm)	215 (6.1)	
SOUND LEVEL (export model only)		
Sound pressure level, Lpa (dbA) (Kpa: ± 10dbA)	58	
ELECTRICAL REQUIREMENTS		
MDE model—voltage	240V/60Hz	
MDG model—voltage	120V/60Hz	
BREAKER/FUSE MIN. REQUIREMENTS		
MDE model—amps	30	
MDG model—amps	15	
ELECTRIC HEATING ELEMENT		
Domestic models—watts	5,600	
Canadian models—watts	5,250	
GAS RATING		
MDG model—BTU/hr. (kcal/hr.)	24,000 (6,048)	
EXHAUST DUCT DIAMETER—IN. (MM)	4 (100)*	
ELECTRONIC BURNER IGNITION		
MDG model	Yes	
GAS INLET		
MDG model—in.	3/8 N.P.T.	
ADJUSTABLE LEVELING LEGS	Yes	
APPROXIMATE WEIGHT		
Crated—lbs. (kg) electric/gas	160 (73)/113 (74)	
Uncrated—lbs. (kg) electric/gas	147 (67)/150 (68)	
DIMENSIONS		
Width—in. (mm)	27 (686)	
Depth—in. (mm)	29 (737)	
Height—in. (mm)	45.75 (1,162)**	
Door opening diameter—in. (mm)	18.25 (464)	
OPTIONAL PEDESTAL ADDS:		
Height—in. (mm)	2.75 (70)	

^{*}Use 4" (100 mm) diameter rigid aluminum or galvanized steel duct. Never use plastic, non-metal or combustible duct.

See specific instructions for proper installation. Because of continuous product improvement, Maytag reserves the right to change specifications without notice.







MAXIMUM EXHAUST DUCT LENGTH PER NUMBER OF TURNS

Number Of 90° Turns







Rigid Metal Vent

	Box Hood and Louvered Style	Angled Hood Style
0	135 ft. (41.2 m)	129 ft. (39.3 m)
1	125 ft. (38.1 m)	119 ft. (36.3 m)
2	115 ft. (35.1 m)	109 ft. (33.2 m)
3	106 ft. (32.3 m)	100 ft. (30.5 m)
4	98 ft. (29.9 m)	92 ft. (28.0 m)

Flexible Metal Vent

	Box Hood and Louvered Style	Angled Hood Style
0	76 ft. (23.2 m)	62 ft. (18.9 m)
1	71 ft. (21.6 m)	57 ft. (17.4 m)
2	67 ft. (20.4 m)	53 ft. (16.2 m)
3	65 ft. (19.8 m)	51 ft. (15.6 m)
4	63 ft. (19.2 m)	49 ft. (14.9 m)









5-YEAR LIMITED WARRANTY ALL PARTS COVERED

For a period from the date of original purchase through the time listed above, the designated parts that fail in normal commercial use will be repaired or replaced free of charge for the part itself, with the owner paying all other costs, including labor, transportation and customs duty. Chemical damage is excluded from all warranty coverage. See complete warranty for details.

^{**}Includes height of metercase.